

Liquid Patch premium quality sealant allows it to remain active for up to five years, instantly sealing punctures over and over again

- Seals punctures by objects up to 6mm diameter
- Suitable for tubed or tubeless tyres



To find how much you need, measure the height and width of your tyre (in cms) and multiply as follows:
 $W \text{ (cm)} \times H \text{ (cm)} \times .5 = \text{required mls}$

Average amount of Liquid Patch required per tyre:

Bicycles, Golf Carts, Wheelchairs	125ml
Farm Trailers, Ride-On Mowers	250ml
Cars, Caravans, Car Trailers	500ml
4WDs, Off-Road Recreational Vehicles	750ml
Trucks and Vans	1000ml

250ml

DIRECTIONS FOR USE:

Note: Never to be diluted. Can not be used with any other sealant.

1. Rotate tyre so valve stem is at either 4 or 8 o'clock.
2. Shake bottle well, then twist cap anti-clockwise and pull to fully extend filling tube.
3. Remove cap using built-in valve core removal tool.
4. Insert cap/valve tool into valve and turn anti-clockwise to remove valve core and fully deflate tyre.
5. Slide filling tube over valve stem and slowly squeeze your required amount of sealant into the tyre, as per the above method. ($W \times H \times .5 = \text{required mls}$).
6. Re-install the valve core using the cap tool, turning clockwise. Do not over tighten.
7. Inflate tyre to the manufacturer's recommended pressure.
8. For optimum results, rotate the wheel multiple times to coat the tyre and activate seal.
9. Rinse bottle and dispose into a recycling bin.

IMPORTANT: If using "on-road" vehicles, check tyre for cuts or other damage. If none, use Liquid Patch as a temporary repair, reduce driving speed to < 80km/h, and have your tyre inspected as soon as possible by a tyre service professional.

Tyre sealants are not designed to Repair damage to Tyre Shoulder and Side Wall, you should seek advice from a tyre service professional.

CONDITION OF SALE: Only to be used in strict accordance with the manufacturer's instructions. The supplier/manufacturer takes no responsibility for any damage, injury, or loss directly or indirectly as a result of the use of this product.

LIQUID PATCH[®]

Stops Flats in its Tracks

- Dual Use Tube & Tyre Sealant
- Fill and forget System Seals while you Drive
- Automatic Puncture Protection



New Safety Lock Cap
 Features Built-in
 Valve Removal Tool
 and Fill in Tube



500ml



CAUTION: KEEP OUT OF REACH OF CHILDREN

SAFETY DIRECTIONS:

Avoid contact with skin and eyes.
 If in eyes, flush well with water.

FIRST AID:

Contact a poisons information centre
 (ph: 131 126 in Australia, or
 0800 764 766 in NZ) or a doctor.

Part No. LP500

Jampactt Pty Ltd
 P.O. Box 4111, Narre Warren Sth
 VICTORIA 3805
 +61 3 5995 1234
 enquiries@liquidpatch.com
 AUSTRALIAN MADE & OWNED



9 331888 000013

www.liquidpatch.com